



US011517437B2

(12) **United States Patent**
Hjelle et al.

(10) **Patent No.:** **US 11,517,437 B2**

(45) **Date of Patent:** ***Dec. 6, 2022**

(54) **CARDIAC TREATMENT SYSTEM**

(71) Applicant: **DiaxaMed, LLC**, Raleigh, NC (US)

(72) Inventors: **Aaron J. Hjelle**, Andover, MN (US);
William E. Cohn, Bellaire, TX (US);
Richard F. Schroeder, Fridley, MN (US);
James F. Buck, Independence, MN (US);
Karl R. Leinsing, Dover, NH (US)

(73) Assignee: **DiaxaMed, LLC**, Pinebluff, NC (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 360 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **16/523,607**

(22) Filed: **Jul. 26, 2019**

(65) **Prior Publication Data**

US 2019/0343636 A1 Nov. 14, 2019

Related U.S. Application Data

(63) Continuation of application No. 15/218,675, filed on Jul. 25, 2016, now Pat. No. 10,405,981, which is a (Continued)

(51) **Int. Cl.**

A61F 2/24 (2006.01)

D04B 21/12 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **A61F 2/2481** (2013.01); **A61M 60/191** (2021.01); **A61M 60/274** (2021.01);

(Continued)

(58) **Field of Classification Search**

CPC **A61F 2/2478**; **A61F 2/2481**; **A61F 2/0013**;
A61F 2/0031; **A61F 2/004**; **A61F 2/0063**;
A61F 5/005; **A61F 5/0063**; **A61M 1/1068**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,682,119 A 8/1928 Field
1,965,542 A 11/1933 Colvin, Jr.
(Continued)

FOREIGN PATENT DOCUMENTS

DE 324524 8/1920
DE 29517393 2/1996
(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 09/635,345, filed Aug. 2000, Chin.
(Continued)


Primary Examiner — Carrie R Dorna

(74) *Attorney, Agent, or Firm* — Fish & Richardson P.C.

(57) **ABSTRACT**

A cardiac device for implantation proximate an exterior of a heart, the cardiac device including an inflatable bladder including an inner wall and an outer wall, wherein the inner wall itself is more expandable than the outer wall itself such that the inflatable bladder itself is configured to deform substantially inwardly to exert localized pressure against a region of the heart when the inflatable bladder is positioned adjacent the region of the heart and inflated.

20 Claims, 3 Drawing Sheets



Related U.S. Application Data

- continuation of application No. 14/053,261, filed on Oct. 14, 2013, now Pat. No. 9,421,101.
- (60) Provisional application No. 61/713,351, filed on Oct. 12, 2012.
- (51) **Int. Cl.**
A61M 60/274 (2021.01)
A61M 60/839 (2021.01)
A61M 60/468 (2021.01)
A61M 60/861 (2021.01)
A61M 60/191 (2021.01)
A61M 60/289 (2021.01)
A61M 60/867 (2021.01)
A61B 90/00 (2016.01)
A61F 2/95 (2013.01)
A61M 60/148 (2021.01)
- (52) **U.S. Cl.**
 CPC *A61M 60/289* (2021.01); *A61M 60/468* (2021.01); *A61M 60/839* (2021.01); *A61M 60/861* (2021.01); *A61M 60/867* (2021.01); *D04B 21/12* (2013.01); *A61B 2090/3966* (2016.02); *A61F 2/9517* (2020.05); *A61F 2002/2484* (2013.01); *A61F 2250/0003* (2013.01); *A61F 2250/0098* (2013.01); *A61M 60/148* (2021.01); *A61M 2205/32* (2013.01); *D10B 2509/08* (2013.01)

References Cited

(56)

U.S. PATENT DOCUMENTS

1,982,207	A	11/1934	Furniss	5,042,463	A	8/1991	Lekholm
2,138,603	A	11/1938	Johnson	5,057,117	A	10/1991	Atweh
2,278,926	A	4/1942	Hartwell	5,064,431	A	11/1991	Gilbertson et al.
2,376,442	A	5/1945	Mehler	5,074,129	A	12/1991	Matthew
2,992,550	A	7/1961	Frith	5,087,243	A	2/1992	Avitall
3,384,530	A	5/1968	Mercer et al.	5,131,905	A	7/1992	Grooters
3,452,742	A	7/1969	Muller	5,150,706	A	9/1992	Cox et al.
3,551,543	A	12/1970	Mercer et al.	5,186,711	A	2/1993	Epstein
3,587,567	A	6/1971	Schiff	5,188,813	A	2/1993	Fairey et al.
3,643,301	A	2/1972	Weigl	5,192,314	A	3/1993	Daskalakis
3,732,662	A	5/1973	Paxton	5,207,725	A	5/1993	Pinkerton
3,768,643	A	10/1973	Bruno	5,224,363	A	7/1993	Sutton
3,811,411	A	5/1974	Moeller	5,256,132	A	10/1993	Snyders
3,983,863	A	10/1976	Janke et al.	5,279,539	A	1/1994	Bohan et al.
4,035,849	A	7/1977	Angell	5,290,217	A	3/1994	Campos
4,048,990	A	9/1977	Goetz	5,336,253	A	8/1994	Gordon et al.
4,196,534	A	4/1980	Shibamoto	5,339,657	A	8/1994	McMurray
4,403,604	A	9/1983	Wilkinson et al.	5,341,815	A	8/1994	Cofone et al.
4,428,375	A	1/1984	Ellman	5,356,432	A	10/1994	Rutkow et al.
D273,514	S	4/1984	Heilman et al.	5,366,460	A	11/1994	Eberbach
4,466,331	A	8/1984	Matheson	5,383,840	A	1/1995	Heilman et al.
4,536,893	A	8/1985	Parravicini	5,385,156	A	1/1995	Oliva
4,567,900	A	2/1986	Moore	5,405,360	A	4/1995	Tovey
4,598,039	A	7/1986	Fischer et al.	5,409,703	A	4/1995	McAnalley et al.
4,630,597	A	12/1986	Kantrowitz et al.	5,429,584	A	7/1995	Chiu
4,637,377	A	1/1987	Loop	5,507,779	A	4/1996	Altman
4,690,134	A	9/1987	Snyders	5,524,633	A	6/1996	Heaven et al.
4,790,850	A	12/1988	Dunn et al.	5,533,958	A	7/1996	Wilk
4,821,723	A	4/1989	Baker, Jr. et al.	5,558,617	A	9/1996	Heilman et al.
4,827,932	A	5/1989	Ideker et al.	5,593,441	A	1/1997	Lichtenstein et al.
4,834,707	A	5/1989	Evans	5,603,337	A	2/1997	Jarvik
4,840,626	A	6/1989	Linsky et al.	5,611,515	A	3/1997	Benderev et al.
4,878,890	A	11/1989	Bilweis	5,647,380	A	7/1997	Campbell et al.
4,932,972	A	6/1990	Dunn et al.	5,695,525	A	12/1997	Mulhauser et al.
4,936,857	A	6/1990	Kulik	5,702,343	A	12/1997	Alferness
4,957,477	A	9/1990	Lundback	5,713,954	A	2/1998	Rosenberg et al.
4,973,300	A	11/1990	Wright	5,735,290	A	4/1998	Sterman et al.
4,976,730	A	12/1990	Kwan-Gett	5,766,216	A	6/1998	Gangal et al.
4,984,584	A	1/1991	Hansen et al.	5,782,746	A	7/1998	Wright
4,995,857	A	2/1991	Arnold	D399,000	S	9/1998	Rothman et al.
				5,800,334	A	9/1998	Wilk
				5,800,528	A	9/1998	Lederman et al.
				5,839,842	A	11/1998	Wanat et al.
				5,848,962	A	12/1998	Feindt
				5,853,422	A	12/1998	Huebsch et al.
				5,928,250	A	7/1999	Koike et al.
				5,931,810	A	8/1999	Grabek
				5,961,440	A	10/1999	Schweich, Jr. et al.
				5,972,013	A	10/1999	Schmidt
				5,976,551	A	11/1999	Mottez et al.
				5,990,378	A	11/1999	Ellis
				6,042,536	A	3/2000	Tihon et al.
				6,045,497	A	4/2000	Schweich, Jr. et al.
				6,050,936	A	4/2000	Schweich, Jr. et al.
				6,059,715	A	5/2000	Schweich, Jr. et al.
				6,076,013	A	6/2000	Brennan et al.
				6,077,214	A	6/2000	Mortier et al.
				6,077,218	A	6/2000	Alferness
				6,085,754	A	7/2000	Alferness et al.
				6,089,051	A	7/2000	Gorywoda et al.
				6,095,968	A	8/2000	Snyders
				6,123,662	A	9/2000	Alferness
				6,126,590	A	10/2000	Alferness
				6,155,968	A	12/2000	Wilk
				6,155,972	A	12/2000	Nauertz et al.
				6,162,168	A	12/2000	Schweich, Jr. et al.
				6,165,119	A	12/2000	Schweich, Jr. et al.
				6,165,120	A	12/2000	Schweich, Jr. et al.
				6,165,121	A	12/2000	Alferness
				6,165,122	A	12/2000	Alferness
				6,169,922	B1	1/2001	Alferness et al.
				6,174,279	B1	1/2001	Girard
				6,179,791	B1	1/2001	Krueger
				6,183,411	B1	2/2001	Mortier et al.
				6,190,408	B1	2/2001	Melvin
				6,193,646	B1	2/2001	Kulisz et al.
				6,193,648	B1	2/2001	Krueger
				6,205,747	B1	3/2001	Paniagua Olacoea
				6,206,004	B1	3/2001	Schmidt et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,206,820 B1	3/2001	Kazi	6,730,016 B1	5/2004	Cox et al.
6,221,103 B1	4/2001	Melvin	6,746,471 B2	6/2004	Mortier et al.
6,224,540 B1	5/2001	Lederman et al.	6,755,777 B2	6/2004	Schweich, Jr. et al.
6,230,714 B1	5/2001	Alferness et al.	6,755,779 B2	6/2004	Vanden Hoek et al.
6,238,334 B1 *	5/2001	Easterbrook, III	6,755,861 B2	6/2004	Nakao
		A61M 60/268	6,764,510 B2	7/2004	Vidlund et al.
		600/16	6,776,754 B1	8/2004	Wilk
6,241,654 B1	6/2001	Alferness	6,793,618 B2	9/2004	Schweich, Jr. et al.
6,260,552 B1	7/2001	Mortier et al.	6,808,488 B2	10/2004	Mortier et al.
6,261,222 B1	7/2001	Schweich, Jr. et al.	6,852,075 B1	2/2005	Taylor
6,264,602 B1	7/2001	Mortier et al.	6,852,076 B2	2/2005	Nikolic et al.
6,293,906 B1	9/2001	Vanden Hoek et al.	6,858,001 B1	2/2005	Aboul-Hosn
6,332,863 B1	12/2001	Schweich, Jr. et al.	6,876,887 B2	4/2005	Okuzumi et al.
6,332,864 B1	12/2001	Schweich, Jr. et al.	6,881,185 B2	4/2005	Vanden Hoek et al.
6,332,893 B1	12/2001	Mortier et al.	6,893,392 B2	5/2005	Alferness
6,360,749 B1	3/2002	Jayaraman	6,896,652 B2	5/2005	Alferness et al.
6,370,429 B1	4/2002	Alferness et al.	6,902,522 B1	6/2005	Walsh et al.
6,375,608 B1	4/2002	Alferness	6,902,524 B2	6/2005	Alferness et al.
6,402,679 B1	6/2002	Mortier	6,908,426 B2	6/2005	Shaplant et al.
6,402,680 B2	6/2002	Mortier	6,951,534 B2	10/2005	Girard et al.
6,406,420 B1	6/2002	McCarthy et al.	6,997,865 B2	2/2006	Alferness et al.
6,409,760 B1	6/2002	Melvin	7,022,063 B2	4/2006	Lau et al.
6,416,459 B1	7/2002	Haindl	7,022,064 B2	4/2006	Alferness et al.
6,425,856 B1	7/2002	Shaplant et al.	7,025,719 B2	4/2006	Alferness et al.
6,432,039 B1	8/2002	Wardle	7,060,023 B2	6/2006	French et al.
6,482,146 B1	11/2002	Alferness et al.	7,077,862 B2	7/2006	Vidlund et al.
6,488,618 B1	12/2002	Paolitto et al.	7,081,086 B2	7/2006	Lau et al.
6,494,825 B1	12/2002	Talpade	7,112,219 B2	9/2006	Vidlund
6,508,756 B1	1/2003	Kung et al.	7,155,295 B2	12/2006	Lau et al.
6,514,194 B2	2/2003	Schweich, Jr. et al.	7,163,507 B2	1/2007	Alferness et al.
6,517,570 B1	2/2003	Lau et al.	7,181,272 B2	2/2007	Struble et al.
6,520,904 B1	2/2003	Melvin	7,189,203 B2	3/2007	Lau et al.
6,537,198 B1	3/2003	Vidlund et al.	7,235,042 B2	6/2007	Vanden Hoek et al.
6,537,203 B1	3/2003	Alferness et al.	7,252,632 B2	8/2007	Shaplant et al.
6,541,678 B2	4/2003	Klein	7,276,022 B2	10/2007	Lau et al.
6,544,168 B2	4/2003	Alferness	7,351,200 B2	4/2008	Alferness
6,547,716 B1	4/2003	Milbocker	7,398,781 B1	7/2008	Chin
6,558,319 B1	5/2003	Aboul-Hosn et al.	7,404,793 B2	7/2008	Lau
6,564,094 B2	5/2003	Alferness et al.	7,410,461 B2	8/2008	Lau et al.
6,567,699 B2	5/2003	Alferness et al.	7,468,029 B1	12/2008	Robertson
6,569,082 B1	5/2003	Chin	7,651,462 B2	1/2010	Hjelle et al.
6,572,533 B1	6/2003	Shaplant et al.	7,955,247 B2	6/2011	Levine et al.
6,575,921 B2	6/2003	Vanden Hoek et al.	8,092,363 B2	1/2012	Leinsing et al.
6,579,226 B2	6/2003	Vanden Hoek et al.	8,100,821 B2	1/2012	Hjelle et al.
6,582,355 B2	6/2003	Alferness et al.	8,109,868 B2	2/2012	Girard et al.
6,587,734 B2	7/2003	Okuzumi et al.	8,202,212 B2	6/2012	Hjelle et al.
6,589,160 B2	7/2003	Schweich, Jr. et al.	8,277,372 B2	10/2012	Alferness et al.
6,592,514 B2	7/2003	Kolata et al.	8,617,051 B2	12/2013	Hjelle et al.
6,595,912 B2	7/2003	Lau et al.	10,806,580 B2	10/2020	Walsh
6,602,184 B2	8/2003	Lau et al.	2001/0016675 A1	8/2001	Mortier et al.
6,612,978 B2	9/2003	Lau et al.	2001/0025171 A1	9/2001	Mortier et al.
6,612,979 B2	9/2003	Lau et al.	2002/0019580 A1	2/2002	Lau et al.
6,616,596 B1	9/2003	Milbocker	2002/0029080 A1	3/2002	Mortier et al.
6,616,684 B1	9/2003	Vidlund et al.	2002/0045798 A1	4/2002	Lau et al.
6,620,095 B2	9/2003	Taheri	2002/0058855 A1	5/2002	Schweich, Jr. et al.
6,622,730 B2	9/2003	Ekvall et al.	2002/0068849 A1	6/2002	Schweich, Jr. et al.
6,629,921 B1	10/2003	Schweich, Jr. et al.	2002/0068850 A1	6/2002	Vanden Hoek et al.
6,645,139 B2	11/2003	Haindl	2002/0077524 A1	6/2002	Schweich, Jr. et al.
6,663,558 B2	12/2003	Lau et al.	2002/0133055 A1	9/2002	Handl
6,673,009 B1	1/2004	Vanden Hoek et al.	2002/0147406 A1	10/2002	Von Segesser
6,682,474 B2	1/2004	Lau et al.	2002/0151766 A1	10/2002	Shaplant
6,682,475 B2	1/2004	Cox et al.	2002/0169358 A1	11/2002	Mortier et al.
6,682,476 B2	1/2004	Alferness et al.	2002/0169359 A1	11/2002	McCarthy et al.
6,685,627 B2	2/2004	Jayaraman	2002/0169360 A1	11/2002	Taylor et al.
6,689,048 B2	2/2004	Vanden Hoek et al.	2002/0173694 A1	11/2002	Mortier et al.
6,695,768 B1	2/2004	Levine et al.	2003/0032979 A1	2/2003	Mortier et al.
6,695,769 B2	2/2004	French et al.	2003/0050529 A1	3/2003	Vidlund et al.
6,701,929 B2	2/2004	Hussein	2003/0060895 A1	3/2003	French et al.
6,702,732 B1	3/2004	Lau et al.	2003/0065248 A1	4/2003	Lau et al.
6,709,382 B1	3/2004	Horner	2003/0088149 A1	5/2003	Raman et al.
6,716,158 B2	4/2004	Raman et al.	2003/0130731 A1	7/2003	Vidlund et al.
6,723,038 B1	4/2004	Schroeder et al.	2003/0166992 A1	9/2003	Schweich, Jr. et al.
6,723,041 B2	4/2004	Lau et al.	2003/0171641 A1	9/2003	Schweich, Jr. et al.
6,726,696 B1	4/2004	Houser et al.	2003/0181928 A1	9/2003	Vidlund et al.
6,726,920 B1	4/2004	Theeuwes et al.	2003/0229260 A1	12/2003	Girard et al.
6,727,316 B1	4/2004	Bremser	2003/0229265 A1	12/2003	Girard et al.
			2003/0233023 A1	12/2003	Khaghani et al.
			2004/0002626 A1	1/2004	Feld et al.
			2004/0010180 A1	1/2004	Scorvo

(56)

References Cited

U.S. PATENT DOCUMENTS

2004/0034272	A1	2/2004	Diaz et al.
2004/0059181	A1	3/2004	Alferness
2004/0127983	A1	7/2004	Mortier et al.
2004/0133062	A1	7/2004	Pai et al.
2004/0133063	A1	7/2004	McCarthy et al.
2004/0147805	A1	7/2004	Lau et al.
2004/0147965	A1	7/2004	Berger
2004/0158123	A1	8/2004	Jayaraman
2004/0167374	A1	8/2004	Schweich et al.
2004/0181118	A1	9/2004	Kochamba
2004/0181120	A1	9/2004	Kochamba
2004/0181124	A1	9/2004	Alferness
2004/0186342	A1	9/2004	Vanden Hoek et al.
2004/0210104	A1	10/2004	Lau et al.
2004/0215308	A1	10/2004	Bardy et al.
2004/0225304	A1	11/2004	Vidlund et al.
2004/0243229	A1	12/2004	Vidlund et al.
2004/0249242	A1	12/2004	Lau et al.
2004/0267083	A1	12/2004	McCarthy et al.
2004/0267329	A1	12/2004	Raman et al.
2005/0004428	A1	1/2005	Cox et al.
2005/0010079	A1	1/2005	Bertolero et al.
2005/0014992	A1	1/2005	Lilip et al.
2005/0020874	A1	1/2005	Lau et al.
2005/0033109	A1	2/2005	Lau et al.
2005/0038316	A1	2/2005	Taylor
2005/0054892	A1	3/2005	Lau et al.
2005/0059853	A9	3/2005	Kochambe
2005/0059854	A1	3/2005	Hoek et al.
2005/0059855	A1	3/2005	Lau et al.
2005/0065396	A1	3/2005	Mortier et al.
2005/0075723	A1	4/2005	Schroeder et al.
2005/0085688	A1	4/2005	Girard et al.
2005/0090707	A1	4/2005	Lau et al.
2005/0133941	A1	6/2005	Schuhmacher
2005/0171589	A1	8/2005	Lau et al.
2005/0192474	A1	9/2005	Vanden Hoek et al.
2005/0228217	A1	10/2005	Alferness et al.
2005/0256368	A1	11/2005	Klenk et al.
2005/0283042	A1	12/2005	Meyer et al.
2005/0288715	A1	12/2005	Lau et al.
2006/0009831	A1	1/2006	Lau et al.
2006/0052660	A1	3/2006	Chin
2006/0063970	A1	3/2006	Raman et al.
2006/0155165	A1	7/2006	Vanden Hoek et al.
2006/0229490	A1	10/2006	Chin
2006/0241748	A1	10/2006	Lee et al.
2006/0270896	A1	11/2006	Dietz et al.
2007/0032696	A1	2/2007	Duong
2007/0043416	A1	2/2007	Callas et al.
2007/0208211	A1	9/2007	Alferness et al.
2007/0208215	A1	9/2007	Hjelle
2007/0219407	A1	9/2007	Vanden Hoek et al.
2007/0225547	A1	9/2007	Alferness et al.
2008/0033234	A1	2/2008	Hjelle et al.
2008/0064917	A1	3/2008	Bar et al.
2009/0062596	A1	3/2009	Leinsing et al.
2009/0131743	A1	5/2009	Hjelle et al.
2010/0004504	A1	1/2010	Callas
2010/0094080	A1	4/2010	Hjelle et al.
2010/0160721	A1	6/2010	Alferness et al.
2010/0185050	A1	7/2010	Alferness et al.
2010/0268019	A1	10/2010	Hjelle et al.
2012/0253112	A1	10/2012	Hjelle et al.
2014/0181124	A1	6/2014	Hofmeier et al.
2019/0358038	A1	11/2019	Hjelle et al.

FOREIGN PATENT DOCUMENTS

EP	0280564	8/1988
EP	0303719	2/1989
EP	0557964	9/1993
GB	2209678	5/1989
JP	01-145066	6/1989
JP	02-271829	11/1990

JP	2002-532189	10/2002
SU	1009457	4/1983
WO	WO 1993/03685	3/1993
WO	WO 1996/16601	6/1996
WO	WO 1996/31175	10/1996
WO	WO 1998/14136	4/1998
WO	WO 1998/29041	7/1998
WO	WO 1998/35632	8/1998
WO	WO 1998/58598	12/1998
WO	WO 1999/44534	9/1999
WO	WO 1999/52470	10/1999
WO	WO 1999/52471	10/1999
WO	WO 2000/02500	1/2000
WO	WO 2000/06026	2/2000
WO	WO 2000/06027	2/2000
WO	WO 2000/06028	2/2000
WO	WO 2000/16700	3/2000
WO	WO 2000/28912	5/2000
WO	WO 2000/28918	5/2000
WO	WO 00/36995	6/2000
WO	WO 2001/02500	1/2001
WO	WO 2001/03608	1/2001
WO	WO 2001/10421	2/2001
WO	WO 2001/67985	9/2001
WO	WO 2001/91667	12/2001
WO	WO 2001/95830	12/2001
WO	WO 2002/13726	2/2002
WO	WO 2002/000099	9/2002
WO	WO 2003/022131	3/2003
WO	WO 2006/023580	3/2006
WO	WO 2008/011411	1/2008
WO	WO 2010/111592	9/2010

OTHER PUBLICATIONS

U.S. Appl. No. 14/053,261, filed Oct. 2013, Hjelle et al.
 U.S. Appl. No. 14/053,587, filed Oct. 2013, Hjelle et al.
 U.S. Appl. No. 14/053,590, filed Oct. 2013, Hjelle et al.
 U.S. Appl. No. 29/469,753, filed Oct. 2013, Hjelle et al.
 U.S. Appl. No. 60/148,130, filed Aug. 1999, Chin.
 U.S. Appl. No. 60/150,737, filed Aug. 1999, Chin.
 Bolling, et al., "Intermediate-Term Outcome of Mitral Reconstruction in Cardiomyopathy", *J Thorac. Cardiovasc. Surg.*, Feb. 1998, 115(2):381-388.
 Bourge, "Clinical Trial Begins for Innovative Device-Altering Left Ventricular Shape in Heart Failure", *UAB Insight*, posted Aug. 8, 2012, retrieved Jun. 17, 2004, <http://www.health.uab.edu/show, 2 pages>.
 Capomolla et al., "Dobutamine and nitroprusside infusion in patients with severe congestive heart failure: Hemodynamic improvement by discordant effects on mitral regurgitation, left atrial function, and ventricular function", *American Heart Journal*, Dec. 1997, 1089-1098.
 Capouya et al., "Girdling Effect of Nonstimulated Cardiomyoplasty on Left Ventricular Function", *Ann Thorac. Surg.*, 1993, 56:867-871.
 Cohn, "The Management of Chronic Heart Failure", *The New England Journal of Medicine*, Aug. 15, 1996, 335(7): 490-498.
 Coletta et al., "Prognostic value of left ventricular volume response during dobutamine stress echocardiography," *European Heart Journal*, Oct. 1997, 18: 1599-1605.
 Daubeney et al., "Pulmonary Atresia/Intact Ventricular Septum: Early Outcome After Right Ventricular Outflow Reconstruction by Surgery or Catheter Intervention," *Supplement to Circulation*, Oct. 15, 1995, 92(8), Abstract 1812.
 DeVries et al., "A Novel Technique for Measurement of Pericardial Balloon," *Am. J Physiol Heart Circ Physiol*, Jan. 2001, 280(6):H2815-H2822.
 Ghanta, et al., "Cardiovascular Surgery: Adjustable, Physiological Ventricular Restraint Improves Left Ventricular Mechanics and Reduces Dilation in an Ovine Model of Chronic Heart Failure," *Circulation*, *JAHA*, 2007, 115:1201-10.
 Guasp., "Una protesis contentiva para el tratamiento de la miocardiopatía dilatada," *Revista Espanola de Cardiologia*, Jul. 1998, 51(7): 521-528.

(56)

References Cited

OTHER PUBLICATIONS

Hamilton et al., "Static and Dynamic Operating Characteristics of a Pericardial Balloon," *J Appl. Physiol.*, Apr. 2001, 90(4):1481-1488.

Hung, et al., "Persistent Reduction of Ischemic Mitral Regurgitation by Papillary Muscle Repositioning: Structural Stabilization of the Papillary Muscle Ventricular Wall Complex," *Circulation, JAHA*, 2007, 116:1-259 1-263.

International Search Report and Written Opinion in International Application No. PCT/US2013/064894, dated Apr. 3, 2014, 27 pages.

International Search Report and Written Opinion in International Application No. PCT/US2013/064895, dated Apr. 21, 2014, 14 pages.

Justo et al., "Outcomes of Transcatheter Perforation of the Right Ventricular Outflow Tract as Primary Management for Pulmonary Valve Atresia in the Newborn," Supplement to *Circulation*, Oct. 15, 1995, 92(8), Abstract 1813.

Kass et al., "Reverse Remodeling From Cardiomyoplasty in Human Heart Failure External Constraint Versus Active Assist," *Circulation*, May 1, 1995, 91(9):2314-2318, retrieved Jan. 16, 2014, <http://circ.ahajournals.org/content/91/9/2314.full>.

Labrousse, Louis et al., "Implantation of a Cardiac Support Device by the 'Parachute-Like' Technique Through Sternal and Trans-Abdominal Approach," Abstract, *94 Programme of the 4th EACTS/ESTS Joint Meeting*, Sep. 28, 2005, Barcelona, Spain.

Lamas, et al., "Clinical Significance of Mitral Regurgitation After Acute Myocardial Infarction," *Circulation—JAHA*, Aug. 5, 1997, 96(3):827-833, retrieved Jan. 16, 2014, <http://circ.ahajournals.org/content/96/3/827.long>.

Lei-Cohen, et al., "Design of a New Surgical Approach for Ventricular Remodeling to Relieve Ischemic Mitral Regurgitation," *Circulation*, Jun. 13, 2000, 101:2756-2763.

Levin et al., "Reversal of Chronic Ventricular Dilation in Patients with End-Stage Cardiomyopathy by Prolonged Mechanical Unloading," *Circulation*, Jun. 1, 1995, 91(11): 2717-2720, retrieved Jan. 16, 2014, <http://circ.ahajournals.org/content/91/11/2717.long>.

Lloyd et al., "The PDA Coil Registry: Report of the First 535 Procedures," Supplement to *Circulation*, Oct. 15, 1995, 92(8), Abstract 1811.

Oh et al., "The Effects of Prosthetic Cardiac Binding and Adynamic Cardio myoplasty in a Model of Dilated Cardiomyopathy," *The Journal of Thoracic and Cardiovascular Surgery*, Jul. 1998, 116(1):148-153.

Pai, et al., "Valvular Egurgitation," *Clinical Science Abstracts*, 2000, 1800-1804.

Paling, "Two-Bar Fabrics (Part-Set Threading)", *Warp Knitting Technology*, Columbine Press (Publishers) Ltd., Buxton, Great Britain, p. III (1970).

Timek, et al., "Pathogenesis of Mitral Regurgitation in Tachycardia Induced Cardiomyopathy," *Circulation—JAHA*, 2001, 104:1-47-I-53.

Vaynblat et al., "Cardiac Binding in Experimental Heart Failure," *Ann. Thorac. Surg.*, 1994, vol. 64, 11 pages.

Vinereanu, et al., "'Pure' diastolic dysfunction is associated with long-axis systolic dysfunction. Implications for the diagnosis and classification of heart failure," *European Journal of Heart Failure*, Aug. 2005, 7(5): 820-828 (Abstract Only).

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 2

CARDIAC TREATMENT SYSTEM**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of U.S. application Ser. No. 15/218,675 filed on Jul. 25, 2016, which claims priority to U.S. application Ser. No. 14/053,261 (now U.S. Pat. No. 9,421,101) filed on Oct. 14, 2013, which claims priority to U.S. Provisional Application Ser. No. 61/713,351 filed on Oct. 12, 2012. The contents of the aforementioned applications are hereby fully incorporated herein by reference.

TECHNICAL FIELD

The present disclosure relates to medical devices for treating heart diseases and valvular dysfunction, including valvular regurgitation.

BACKGROUND OF THE INVENTION

Various compression-style systems currently exist for treating heart diseases and conditions such as congestive heart disease and valvular dysfunction. These systems typically involve either: (a) jackets that are placed around the heart to limit heart expansion to treat congestive heart disease, or (b) bands that are placed around the heart with fillable chambers to exert localized pressure to re-form the shape of heart valves, for example to minimize valve leakage.

An example of the former is found in the Acorn Cardiovascular Inc. system set forth in U.S. Published Patent Application 2010/0160721 entitled "Cardiac Support Device With Differential Compliance." This device is used to treat congestive heart disease. Congestive heart disease is the progressive enlargement of the heart. This enlargement requires the heart to perform an increasing amount of work. In time, the heart cannot supply an adequate amount of blood, resulting in a patient that is fatigued and in discomfort. The Acorn Cardiovascular Inc. system is a cardiac support device that limits heart expansion using a flexible jacket positioned around the heart. In operation, the jacket surrounds the myocardium and provides reduced expansion of the heart during diastole. The jacket has upper and lower ends. The upper end is open. The lower end may be open or closed. The jacket is sized for the particular heart to be contained within its volume. When placed on the heart, the upper end of the jacket extends up to the valvular annulus and terminates along the AV groove. The jacket itself further extends down to constrain the lower ventricular extremities. In this position, the jacket provides sufficient constraint at the valvular annulus. Alternatively, the jacket may not cover the apex of the heart (but it will cover its left and right ventricles). This placement is desirable as it presents a constraint against enlargement of the ventricular walls of the heart. After the jacket is positioned on the heart, it can then be secured to the heart, for example, by suturing at various locations around its circumference. However, it is preferred to avoid excessive suturing locations as this would restrict contraction of the heart during systole. Once placed, the jacket's volume and shape can be adjusted by gathering together and suturing excess material. Specifically, the jacket is adjusted to be snug during diastole (without being too tight such that left ventricular pressure will rise). The jacket then constrains enlargement of the heart beyond this volume.

An example of the second type of system is found in Mardil, Inc.'s U.S. Pat. No. 8,092,363 entitled "Heart Band With Fillable Chambers To Modify Heart Valve Function." This device has a plurality of fillable chambers that exert inward radial forces on heart valves. These fillable chambers are disposed within the inner and outer layers of a silicone rubber band. In operation, this device is used to treat dilation of heart valves by applying localized pressure to the surface of the heart. For example, a pair of these fillable chambers positioned on either side of the mitral valve can be used to re-shape the mitral valve such that mitral valve leakage is minimized or stopped.

As can be seen, these two above systems operate quite differently on the patient's heart. The first (i.e.: Acorn) system stabilizes the base of the heart, but does not provide localized therapeutic pressure on the heart valves. The second (i.e. Mardil) system provides localized pressure to heart valves through all heart phases; however, it does not stabilize the base of the heart.

It would instead be desirable to provide a system that permits localized pressure on selected regions of the heart (similar to the Mardill '363 device), but avoids its use of a solid silicone rubber band wrapped around the heart that may interfere with contraction and dilation.

It would also be advantageous to provide a system that provides localized pressure on the heart and also offers the advantages of a knit mesh jacket. Advantages of a knit mesh could include the fact that it allows for more freedom in heart contraction and dilation. In addition, a mesh band will advantageously self-attach to the heart by way of fibrotic encapsulation. This would assist in positioning the inflatable bladder(s) at a desired location and preventing unwanted movement of the bladder(s) in the future.

SUMMARY

In preferred aspects, some embodiments described herein provide a mesh structure (which may be polyester) to position a bladder for deformation of the mitral valve or papillary muscle to decrease valvular regurgitation.

Particular embodiments of the present invention provide a system for providing localized pressure on regions of a patient's heart to treat various heart problems. In various applications, it can be used to apply pressure to the mitral valve to reshape the valve and prevent mitral regurgitation, or to the papillary muscle to prevent mitral regurgitation (by relieving tension on the chordae which prohibits proper valve function), or to the tricuspid valve to prevent regurgitation. With regard to the mitral valve, the anatomical target for deformation is the P2 area of the valve. By pressing on this spot, the distance across the valve is artificially reduced, thereby preventing the gap in the valve responsible for the regurgitation.

In preferred embodiments, the system comprises a jacket received around the heart, with one or more inflatable bladders positioned inside this jacket. The bladder(s) are differentially expandable such that they have an inner (heart-facing) surface that is more compliant than their outer (jacket-facing) surface. As a result, when the bladder(s) is inflated, its inner surface expands more than its outer surface (which may not expand at all). As such, the inflated bladder exerts an inward pressure on a localized region of the heart.

In one aspect, some embodiments described herein provide an assembly for providing localized pressure to a region of a patient's heart to improve heart functioning, comprising: (a) a jacket made of a flexible biocompatible material, the jacket having an open top end that is received around the

heart and a bottom portion that is received around the apex of the heart; and (b) at least one inflatable bladder disposed on an interior surface of the jacket, the inflatable bladder having an inelastic outer (jacket facing) surface positioned adjacent to the jacket and an elastic inner (heart facing) surface such that inflation of the bladder causes the bladder to deform substantially inwardly to exert localized pressure against a region of the heart.

In another aspect, particular embodiments of the present invention provide a method of providing localized pressure to a region of a patient's heart to improve heart functioning, comprising: (a) positioning an assembly around a patient's heart, wherein the assembly comprises: a jacket and at least one inflatable bladder, wherein the jacket is made of a flexible biocompatible material having an open top end that is received around the heart and a bottom portion that is received around the apex of the heart, and the inflatable bladder is disposed on an interior surface of the jacket, the inflatable bladder having an inelastic outer surface positioned adjacent to the jacket and an elastic inner surface; and (b) inflating the bladder causing the bladder to expand such that the bladder deforms substantially inwardly to exert localized pressure against a region of the heart.

An important advantage of some embodiments of the system described herein not seen in existing systems is that its bladder(s) are differentially expandable, meaning that one side of the bladder expands more than the other when it is inflated. This provides very precisely targeted pressure to specific regions of the heart.

Another advantage of the some embodiments of the system described herein is that it uses a mesh jacket to support and position the inflatable bladder(s). An advantage of using a knit mesh (as opposed to a polymer band) to hold the bladder in position is that the mesh is self-attaching to the heart (i.e.: after fibrotic encapsulation). Moreover, there is an anticipated benefit for many patients as the mesh jacket can itself be used to treat the problem of congestive heart disease concurrently with bladder(s) treating valve leakage problems.

In preferred embodiments, the jacket has an elastic band with radiopaque markers at its open top end. With these features, the jacket can then be easily guided and placed at the heart's A-V groove. This makes it easy to position the inflatable bladder(s) at the desired locations on the patient's heart.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 A is a perspective view of the present assembly positioned on a patient's heart, showing an inflatable bladder positioned adjacent to the mitral valve.

FIG. 1 B is a view similar to FIG. 1 A, but showing three optional bladder locations at the mitral valve, papillary muscle and tricuspid valve.

FIG. 2 is a sectional elevation view through one of the inflatable bladders.

DETAILED DESCRIPTION

Particular embodiments of the present invention provide an assembly for providing localized pressure to a region of a patient's heart. As will be described below, some embodiments described herein provide a jacket with one or more inflatable bladders received therein. Thus, the bladder(s) are positioned between the patient's heart and the jacket when the jacket is slipped over the heart.

FIGS. 1A and 1B show embodiments having one or more inflatable bladders, as follows. In FIG. 1A, the inflatable bladder is positioned adjacent to the patient's mitral valve. FIG. 1B shows additional placement locations of bladders adjacent to the papillary muscle and tricuspid valve. It is to be understood that the description herein encompasses embodiments with only one or with more than one inflatable bladder. Thus, FIGS. 1A and 1B simply show preferred locations for the bladder placement(s).

As seen in FIGS. 1A-B and 2, the depicted embodiment provides an assembly comprising: a jacket 10 and at least one inflatable bladder 20. Jacket 10 is made of a flexible biocompatible material and has an open top end 12 that is received around the heart H and a bottom portion 14 that is received around the apex A of the heart. In optional aspects, jacket 10 may be made of a knit mesh. This knit mesh may optionally be made of a polymer, including but not limited to high-density polyethylene. Alternatively, jacket 10 may be made of metal.

In one preferred embodiment, jacket 10 is made of a suitable knit material. An example of such a knit material may be the well known "Atlas Knit" material, being a knit structure formed from generally inelastic fibers. In an Atlas Knit, the fibers are interwoven into sets of parallel spaced-apart strands. In response to the low pressures of the heart during diastole, the fibers are generally non-elastic. Alternatively, jacket 10 may be elastic. Optionally, the fibers may be made of Denier polyester. However, other suitable materials, including but not limited to, PTFE, ePTFE, polypropylene and stainless steel may also be used. Advantages of using a knit material include flexibility, fluid permeability and minimizing the amount of heart surface area in direct contact with the jacket (thereby minimizing the potential of scar tissue development).

Inflatable bladder 20 is disposed on an interior surface of jacket 10. Bladder 20 may or may not be attached to jacket 10. FIG. 1B illustrates three separate inflatable bladders 20, being positioned at the mitral valve (bladder 20A), the papillary muscle (bladder 20B) and the tricuspid valve (bladder 20C). When bladder 20 is positioned adjacent to the mitral valve, it is preferably positioned at the P2 area of the valve (in the center of the posterior leaflet) to reduce the distance across the valve, thereby reducing the gap in the valve responsible for the regurgitation. When bladder 20 is positioned adjacent to the tricuspid valve, it performs a similar function, reducing regurgitation through the tricuspid valve. When bladder 20 is positioned adjacent to the papillary muscle, it gently corrects papillary muscle position and relieves tension on the chordae (which otherwise prohibits normal valve functioning).

As seen in FIG. 2, inflatable bladder 20 has an inelastic outer surface 22 positioned adjacent to jacket 10 and an elastic inner surface 24 positioned adjacent to the heart. Bladder 20 may optionally be made of silicon. In preferred aspects, jacket 10 is inelastic, the outer surface 22 of bladder 20 positioned adjacent to the bladder is inelastic and the inner surface 24 of bladder 10 is elastic. As a result, when inflated through fluid supply line 25, inflation of bladder 20 causes the bladder to deform substantially inwardly (i.e.: towards the heart). This then exerts localized pressure against a region of the heart. As can be seen, supply line(s) 25 are preferably positioned inside jacket 10 and extend out of an open bottom end 13 of the jacket adjacent to the apex of the heart. Bottom end 13 may be cinched closed after the jacket 10 has been positioned around the heart.

In preferred aspects, bladder 20 may be is inflated with fluids including air, inert gasses (such as fluorocarbons),

5

silicone gel, saline and contrast agents. Supply lines **25** may optionally be inflated through a blunt needle port, a Luer port fitting, a subcutaneous port **26**, etc. Supply lines **25** are made of a suitable bio-compatible material, including but not limited to silicone. The present invention preferably includes mechanisms for inflating and deflating bladders **20** post-implementation. For example, in one approach the device is first received onto the heart. After a period of time (e.g.: 30 days) fibrotic encapsulation of mesh jacket **10** will have occurred. At this time, the bladder(s) **20** can then be inflated (through supply line **25** using a needle to percutaneously access filling reservoir **26**. Thus, subcutaneous ports **26** are useful for percutaneous inflation and deflation for therapy optimization or abandonment. Alternatively, the fluid path tube may stay in the intercostal space and be accessed by a small “cut-down” procedure to access the tube.

In optional embodiments, jacket **10** has an elastic band **14** passing around its top end **12**. In addition, radiopaque markers **15** can also be provided around top end **12**.

The present jacket and bladder system can be placed around the patient’s heart in a variety of different approaches. In a preferred method of use, the present system further includes a delivery device for positioning the jacket onto the heart. Exemplary jacket designs and methods of placement are illustrated in US Published Patent Application 2010/0160721, incorporated herein by reference in its entirety. In one preferred aspect of the method, the assembly is implanted into the patient in a left intercostal mini-thoracotomy using contrast pericardiography and fluoroscopic visualization. After opening the parietal pericardium, the lower portion of the heart is free for applying the jacket over the apex. An example system for positioning the jacket is found in U.S. Pat. No. 5,702,343, incorporated herein by reference.

Particular embodiments described herein also include a preferred method of providing localized pressure to a region of a patient’s heart H to improve heart functioning, by: (a) positioning an assembly around a patient’s heart, wherein the assembly comprises: a jacket **10** and at least one inflatable bladder **20**, wherein jacket **10** is made of a flexible biocompatible material having an open top end **12** that is received around the heart and a bottom portion **14** that is received around the apex of the heart, and the inflatable bladder **20** is disposed on an interior surface of the jacket, and the inflatable bladder **20** has an inelastic outer surface positioned adjacent to the jacket and an elastic inner surface. Next, bladder **20** is inflated causing it to expand such that the bladder deforms substantially inwardly to exert localized pressure against a region of the heart.

In another method of use, Pericardial Edge Management Strips (PEMS) are used. PEMS are sheets having one “peel and stick” side, and may be made of Teflon. These sheets can be used to keep the opening into the pericardium open to facilitate insertion of the device without damage to the pericardium (i.e.: the insertion tool getting hung up on the edges of the opening). In addition, Epicardial Management Strips (EMS) can be used to initially separate the heart from the mesh fabric. After the EMS are pulled out, the jacket fabric can then engage the heart.

An example of a suitable system for measuring the size of the heart is illustrated in International Patent Publication WO 2010/111592, entitled Intra-Operative Heart Size Measuring Tool. This device has a flexible measuring cord with length indicia that is placed around the heart. The distal end of the tool can be inserted through an opening in the patient’s chest and pericardium and then positioned at a

6

measurement position at the apex of the patient’s heart. Circumference measurements can be made at the A-V groove or at other heart locations, as desired.

What is claimed is:

1. A cardiac device for implantation adjacent an exterior of a heart, the cardiac device comprising:
 - a jacket configured for implantation circumferentially around ventricles of the heart;
 - an inflatable bladder comprising an inner wall and an outer wall, wherein the inner wall itself is more expandable than the outer wall itself such that the inflatable bladder itself, without any effect to the outer wall from the jacket, deforms substantially inwardly to exert localized pressure against a region of the heart when the inflatable bladder is positioned adjacent the region of the heart and inflated.
2. The cardiac device of claim 1, wherein the region of the heart comprises a mitral valve of the heart.
3. The cardiac device of claim 1, wherein:
 - the inflatable bladder comprises a first inflatable bladder; the region comprises a first region; and
 - the cardiac device further comprises a second inflatable bladder configured to exert localized pressure against a second region of the heart when the second inflatable bladder is positioned adjacent the second region of the heart and inflated.
4. The cardiac device of claim 3, wherein the second region comprises a papillary muscle of the heart.
5. The cardiac device of claim 3, further comprising a third inflatable bladder configured to exert localized pressure against a third region of the heart when the third inflatable bladder is positioned adjacent the third region of the heart and inflated.
6. The cardiac device of claim 5, wherein the third region of the heart comprises a tricuspid valve of the heart.
7. The cardiac device of claim 1, wherein the jacket defines an open top end configured to be positioned in an atrial-ventricular (A-V) groove of the heart, and wherein the inflatable bladder is positioned adjacent the jacket.
8. The cardiac device of claim 7, wherein the inflatable bladder is located such that, when the top end of the jacket is in the A-V groove, the inflatable bladder is positionable adjacent to a mitral valve of the heart.
9. The cardiac device of claim 7, wherein the inflatable bladder is attached to the jacket.
10. The cardiac device of claim 1, further comprising a fluid supply line configured to be coupled to the inflatable bladder and provide fluid to the inflatable bladder.
11. The cardiac device of claim 1, wherein the inflatable bladder is unattached to the jacket.
12. A method of providing localized pressure to one or more regions of a heart to improve heart functioning, the method comprising:
 - a) positioning a cardiac device adjacent the heart, wherein the cardiac device comprises:
 - a jacket configured for implantation circumferentially around ventricles of the heart;
 - an inflatable bladder comprising an inner wall and an outer wall, wherein the inner wall itself is more expandable than the outer wall itself such that the inflatable bladder itself, without any effect to the outer wall from the jacket, deforms substantially inwardly to exert localized pressure against a region of the heart when the inflatable bladder is positioned adjacent the region of the heart and inflated; and

(b) inflating the inflatable bladder such that the inflatable bladder exerts localized pressure to the region of the heart.

13. The method of claim 12, wherein:
 the inflatable bladder comprises a first inflatable bladder; the region comprises a first region; and
 the method further comprises inflating a second inflatable bladder of the cardiac device to exert a localized pressure against a second region of the heart.

14. The method of claim 13, wherein:
 the first region comprises a mitral valve of the heart;
 the second region comprises a papillary muscle of the heart; and

wherein inflating the first inflatable bladder reshapes the mitral valve and inflating the second inflatable bladder repositions the papillary muscle to relieve tension on chordae of the mitral valve.

15. The method of claim 14, further comprising inflating a third inflatable bladder of the cardiac device to exert a localized pressure on a third region of the heart.

16. The method of claim 15, wherein the third region comprises a tricuspid valve of the heart.

17. The method of claim 12, wherein said inflating the inflatable bladder occurs after fibrotic encapsulation.

18. The method of claim 12, wherein the jacket defines an open top end configured to be positioned in an atrial-ventricular (A-V) groove of the heart, and wherein the inflatable bladder is positioned adjacent the jacket.

19. The method of claim 12, wherein inflating the inflatable bladder comprises filling the inflatable bladder with a fluid via a fluid supply line coupled to the inflatable bladder.

20. The method of claim 12, wherein inflating the inflatable bladder comprises filling the inflatable bladder with at least one of a group consisting of: air, inert gas, silicone gel, saline, and contrast agents.

* * * * *